# **Technical data sheet** Cable tray BKRS 100 FS

**Item number: 6062004** 





Heavy-duty, walkable cable tray system BKRS with base perforation, in 100 mm side height.

The cable tray has connector perforations on both sides.

Straight connectors should be ordered separately and in the appropriate quantity. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

ψCE

Steel

Strip galvanized

### Master data

Item number	6062004
Type	BKRS 1030 FS
Description 1	Cable tray BKRS
Description 2	walkable
Manufacturer	OBO
Dimension	100x300x3000
Colour	zinc
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	3
Unit of quantity	Metre
Weight	761.267 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to- Gate	18,0516 kg CO2e / 1 Meter

# **Technical data sheet Cable tray BKRS 100 FS**





## Dimensions



Length	3,000 mm
Length	10 ft
Width	300 mm
Width	12 in
Height	100 mm
Height	4 in
Plate thickness	0.08 in
Plate thickness	2 mm
Dimension B	300 mm
Dimension H	100 mm
Dimension L	3,000 mm
	•

#### Technical data

Connector version	Without connectors
Mounting system fastening type	Floor
Walkable	yes
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	258 cm <sup>2</sup>
Usable cross-section	25752 mm²
Rustproof steel, pickled	no
Side perforation	no
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed