# **Technical data sheet**

# Junction box, B 9/K M empty, with thread

**Item number: 2001942** 





Protection rating IP67, empty box for use with individual terminals, four plastic cover screws, thus absolute corrosion-protection, two fastening bases for screws of up to 5 mm Ø, 7 break-out entries with thread M20 x 1.5. 3 polyamide cable glands for cable diameters of 9–12 mm, type 106 M.

Clear internal dimensions: 84x84x34 mm.

3 cable glands of polyamide for a cable diameter of 9–12 mm, type 106/20 B9K  $\,\mathrm{M}$ 



Duroplast, Aminoplast

| Master data |  |                                 |
|-------------|--|---------------------------------|
|             | Item number                            | 2001942                         |
|             | Туре                                   | B 9 K M                         |
|             | Description 1                          | Junction box                    |
|             | Description 2                          | with 3 cable glands             |
|             | Manufacturer                           | OBO                             |
|             | Dimension                              | 94x94x45                        |
|             | Colour                                 | Light grey; RAL 7035            |
|             | Material                               | Duroplast, Aminoplast Typ 131.5 |
|             | Smallest sales unit                    | 5                               |
|             | Unit of quantity                       | Piece                           |
|             | Weight                                 | 13.5 kg                         |
|             | Weight unit                            | kg/100 pc.                      |
|             | CO2 Footprint (GWP) Cradle-to-<br>Gate | 0,5548 kg CO2e / 1 Piece        |

# **Technical data sheet**

### Junction box, B 9/K M empty, with thread

<sub>0</sub>





# Dimensions Length 94 mm Width 94 mm Height 45 mm

#### **Technical data**

B9/K

OBO

102

| Expandable                     | no  |  |
|--------------------------------|---|--|
| No. of entries                 | 7   |  |
| Type of entry                  | Gland   |  |
| Type of entry                  | Cable   |  |
| Type of housing penetration    | Thread and pre-marking                                    |  |
| Measured insulation voltage Vi | 400 V   |  |
| Cover                          | Not transparent   |  |
| Cover fastening                | Screwed   |  |
| Entry from rear                | no  |  |
| Entries                        | 7 break-out entries with thread M20 x 1.5.                |  |
| Explosion-tested version       | no  |  |
| Flame-resistant                | Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C |  |
| Shape                          | Square  |  |
| Maintain electrical functions  | Without   |  |
| For Ex zone                    | Without   |  |
| For Ex zone gas                | Without   |  |
| For Ex zone dust               | Without   |  |
| for pipe diameter              | 20 mm   |  |
| Halogen-free                   | yes   |  |
| Clear internal dimensions      | 84x84x34 mm   |  |
| With screening                 | no  |  |
| with lid                       | yes   |  |
| Nominal cross-section, max.    | 70 mm²  |  |
| Nominal cross-section, min.    | 0 mm <sup>2</sup>   |  |
| Nominal voltage                | 400 V   |  |
| Sealable                       | yes   |  |
| Impact-resistant               | no  |  |
| Protection rating              | IP67  |  |
| Transparent lid                | no  |  |
| Weatherproof                   | no  |  |