


Technical data sheet

Profile rail CL2712, slot 12 mm, FT, unperforated

Item number: 1109022



Light-duty C profile rail for cable routing, in conjunction with series clips or clamp clips with N foot. Can also be used in building of control cabinets.



St

Steel

FT

Hot-dip galvanised

Master data		
Item number	1109022	
Type	CL2712UP2000FT	
Description 1	Profile rail	
Description 2	unperforated, slot 12mm	
Manufacturer	OBO	
Dimension	2000x27x12,5	
Material	Steel	
Surface	Hot-dip galvanised	
Surface standard	DIN EN ISO 1461	
Smallest sales unit	2	
Unit of quantity	Metre	
Weight	90 kg	
Weight unit	kg/100 m	
CO2 Footprint (GWP) Cradle-to-Gate	1,8227 kg CO2e / 1 Meter	


Technical data sheet

Profile rail CL2712, slot 12 mm, FT, unperforated

Item number: 1109022



Dimensions



Length	2,000 mm
Width	27 mm
Height	12.5 mm
Dimension L	2,000 mm

Technical data

Breakable	no
Type of perforation	Without
Version for	Single profile
Bundle	20 m
Maintain electrical functions	no
Material thickness	2 mm
With perforation	no
With toothing	no
Profile shape	C profile
Slot width	12 mm
Static value A	1.08 cm ²
Static value Iz	0.98 cm ⁴