Technical data sheet

Service pole, type ISSRM45

Item number: 6290087



ISS aluminium service pole with a 45 mm system opening.

Set consists of:

1 one-compartment pole with clamping fastening

Total length: 3,315 mm-3,480 mm

1 ceiling attachment with clamping device

1 aluminium cover

Length: 3,000 mm

The design of this ISS service pole is based on an extremely slender, round aluminium profile, which has a smooth cover of the Rapid 45 device installation trunking series as its front side. The 45 mm system opening is suitable for direct acceptance of Modul 45® switching and connection devices.



Αlι

Aluminium

EL

Anodised

Master data

Item number	6290087
Туре	ISSRM45EL
Description 1	Service pole
Description 2	floor/ceiling
Manufacturer	OBO
Dimension	3000x70x59
Colour	aluminium
Material	Aluminium
Surface	Anodised
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	510 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	109,0436 kg CO2e / 1 Piece

Technical data sheet

Service pole, type ISSRM45

Item number: 6290087



Dimensions Length Width 70 mm Height 59 mm

T	l :		_	
Tec	nnı	cal		ата

Number of compartments Version for Fastening type Floor mounting Ceiling mounting Continuous profile Halogen-free Height compensation, max. Height compensation, min. Cable entry Cover width Changes according to location Pole shape Pole height, min. Adjustable Pre-wired 1 St. St. 1 St.	Number of usable covers	1
Version for Single-sided Fastening type Tension Floor mounting yes Ceiling mounting yes Continuous profile yes Halogen-free yes Height compensation, max. 480 mm Height compensation, min. 315 mm Cable entry Top Cover width 45 mm Changes according to location no Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes		•
Fastening type Floor mounting Ceiling mounting Ves Continuous profile Halogen-free Height compensation, max. Height compensation, min. Cable entry Cover width Changes according to location Pole shape Pole height, max. Pole height, min. Adjustable Tension Yes Tension Yes Tension Yes 480 mm At 90 mm Top Top Top Top Top Top Top Top Top To	Number of compartments	1 St.
Floor mounting yes Ceiling mounting yes Continuous profile yes Halogen-free yes Height compensation, max. 480 mm Height compensation, min. 315 mm Cable entry Top Cover width 45 mm Changes according to location no Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Version for	Single-sided
Ceiling mounting yes Continuous profile yes Halogen-free yes Height compensation, max. 480 mm Height compensation, min. 315 mm Cable entry Top Cover width 45 mm Changes according to location no Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Fastening type	Tension
Continuous profile yes Halogen-free yes Height compensation, max. 480 mm Height compensation, min. 315 mm Cable entry Top Cover width 45 mm Changes according to location no Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Floor mounting	yes
Halogen-free yes Height compensation, max. 480 mm Height compensation, min. 315 mm Cable entry Top Cover width 45 mm Changes according to location no Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Ceiling mounting	yes
Height compensation, max. Height compensation, min. Cable entry Cover width Changes according to location Pole shape Pole height, max. Pole height, min. Adjustable 480 mm 315 mm no Round 908 Height, min. 3315 mm Adjustable 480 mm 3480 mm 3315 mm yes	Continuous profile	yes
Height compensation, min. Cable entry Cover width Changes according to location Pole shape Pole height, max. Pole height, min. Adjustable 315 mm Top As mm As min. A	Halogen-free	yes
Cable entry Cover width 45 mm Changes according to location Pole shape Round Pole height, max. Pole height, min. Adjustable yes	Height compensation, max.	480 mm
Cover width 45 mm Changes according to location no Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Height compensation, min.	315 mm
Changes according to location no Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Cable entry	Тор
Pole shape Round Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Cover width	45 mm
Pole height, max. 3480 mm Pole height, min. 3315 mm Adjustable yes	Changes according to location	no
Pole height, min. 3315 mm Adjustable yes	Pole shape	Round
Adjustable yes	Pole height, max.	3480 mm
_ 1	Pole height, min.	3315 mm
Pre-wired no	Adjustable	yes
	Pre-wired	no