

Technical data sheet

UTC4 W with 2 protective contact sockets, orange

Item number: 7404613



The ready-for-connection UTC4 universal support has 2 pre-installed 33° protective contact sockets of 16 A and 2 blanking covers for reinstallation of 2 installation devices of the Modul 45 series. Suitable for VL connection cables and device installation units of nominal size R7, R9 and 9.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI.
The ready-for-connection UTC4 universal support has 2 pre-installed 33° protective contact sockets of 16 A and 2 blanking covers for reinstallation of 2 installation devices of the Modul 45 series.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI

PA

Polyamide

Master data		
Item number	7404613	
Type	UTC4 W OR2	
Description 1	Universal supportConnectWINSTA	
Description 2	double orange	
Manufacturer	OBO	
Dimension	208x76x45	
Material	Polyamide	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	30.7 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to-Gate	1,0084 kg CO2e / 1 Piece	


Technical data sheet

UTC4 W with 2 protective contact sockets, orange

Item number: 7404613



Dimensions



Length	218 mm
Width	76 mm
Height	60 mm

Technical data

Connection cable, halogen-free	no
Number of installable devices	4
Version for	Double pure orange
Cable length	300 mm
Line cross-section	2.5 mm ²
Plug-in system	WINSTA® MIDI
Plug connector system, system-specific	yes
Circuit	1
System length	208 mm
Surge protection	no